

In the Claims

Please amend the claims as detailed herein:

1. (Currently amended) A hand-held grinding tool for sharpening a work piece comprising:

an oscillatory drive having a drive shaft which is driven oscillatingly back and forth about a longitudinal axis thereof;

a holder for mounting a working part being configured as a grinding plate having a flat grinding surface;

a fixed holding section provided on said holder and a removable clamping part provided on said holder for clamping said working part at one end thereof between said fixed holding section and said removable clamping part; and

at least one tensioning part for fixing said working part between said fixed holding section and said removable clamping part of said holder in a position so that said grinding surface extends in a plane substantially perpendicularly to said drive shaft;

wherein said clamping part has a generally triangular ~~shape~~ cross section comprising an outer surface which serves as a guide surface for supporting a surface of said work piece to define a predetermined angle between said surface of said work piece and said grinding surface of said working part when guiding said grinding tool along said surface of said work piece for sharpening said work piece;

wherein said predetermined angle is between 10° and 40°.

2. (Previously Presented) The grinding tool of claim 4, wherein said predetermined angle is between 10° and 40°.

3. (Previously Presented) The grinding tool of claim 1, wherein said predetermined angle is about 15°.

4. (Currently amended) A hand-held grinding tool for sharpening a work piece comprising:

an oscillatory drive having a drive shaft which is driven oscillatingly about a longitudinal axis thereof;

a holder for mounting a working part being configured as a grinding plate having a flat grinding surface;

a fixed holding section provided on said holder and a removable clamping part provided on said holder for clamping said working part at one end thereof between said fixed holding section and said removable clamping part; and

at least one tensioning part for fixing said working part between said fixed holding section and said removable clamping part of said holder in a position so that said grinding surface extends in a plane substantially perpendicularly to said drive shaft;

wherein said clamping part comprises an outer surface which serves as a guide surface for supporting a surface of said work piece to define a predetermined angle between said surface of said work piece and said grinding surface of said working part when guiding said grinding tool along said surface of said work piece for sharpening said work piece;

wherein said grinding tool comprises a plurality of different clamping parts designed for different predetermined angles and being exchangeable so as to allow a setting of the predetermined angle.

5. (Previously Presented) The grinding tool of claim 1, wherein said clamping part comprises an outer surface that ends toward said flat grinding surface in a partially circular arc when said working part is clamped between said holding section and said clamping part.

6. (Original) The grinding tool of claim 5, wherein said holder comprises a mounting opening for mounting said grinding tool on said drive shaft of said oscillatory drive.

7. (Original) The grinding tool of claim 6, wherein said circular arc defines a centre which is located within a centre of said mounting opening.

8. (Original) The grinding tool of claim 1, wherein said grinding plate comprises two outer surfaces each of which is configured as a grinding surface.

9. (Original) The grinding tool of claim 8, wherein said two grinding surfaces protrude to the outside beyond said fixed holding section and beyond said clamping part.

10. (Previously Presented) The grinding tool of claim 1, wherein said working part comprises at least one grinding surface having a coating comprising diamond abrasive particles.

11. (Previously Presented) The grinding tool of claim 1, wherein said working part comprises at least one grinding surface having a coating comprising hard metal abrasive particles.

12. (Original) The grinding tool of claim 1, wherein said holding section of said holder comprises threaded holes for receiving tensioning parts configured as screws.

13. (Original) The grinding tool of claim 12, wherein said clamping part comprises recesses configured for receiving screws in a sunk-in configuration.

14. (Currently amended) A holder in a grinding tool for sharpening a work piece using an a hand-held oscillatory drive having a drive shaft which is driven oscillatingly back and forth about a longitudinal axis thereof, wherein:

said holder is configured for mounting a working part to said drive shaft of said oscillatory drive, said working part being configured as a grinding plate having a flat grinding surface;

said holder comprises a fixed holding section and a removable clamping part for clamping said working part at one end thereof between said fixed holding section and said removable clamping part;

said holder comprises at least one tensioning part for fixing said working part between said fixed holding section and said removable clamping part of said holder in a position so that said grinding surface extends in a plane substantially perpendicularly to said drive shaft;

wherein said clamping part has a generally triangular shape cross section comprising an outer surface which serves as a guide surface for supporting a surface of said work piece to define a preset angle between said surface of said work piece and said grinding surface of said working part when guiding said grinding tool along said surface of said work piece for sharpening said work piece; and

wherein said preset angle is between 10° and 40°.

15. (Currently amended) A hand-held grinding tool for sharpening a work piece comprising:

an oscillatory drive having a drive shaft which is driven oscillatingly back and forth about a longitudinal axis thereof;

a holder for mounting a working part being configured as a grinding plate having a flat grinding surface;

a fixed holding section provided on said holder and a removable clamping part provided on said holder for clamping said working part at one end thereof between said fixed holding section and said removable clamping part;

at least one tensioning part for fixing said working part between said fixed holding section and said removable clamping part of said holder in a position so that said grinding surface extends in a plane substantially perpendicularly to said drive shaft;

wherein said clamping part has a generally triangular ~~shape~~ cross section comprising an outer surface which serves as a guide surface for supporting a surface of said work piece to define a predetermined angle between said surface of said work piece and said grinding surface of said working part when guiding said grinding tool along said surface of said work piece for sharpening said work piece;

and wherein said grinding surface protrudes beyond said outer surface of said clamping part.

16. (Previously Presented) The grinding tool of claim 15, wherein said predetermined angle is between 10° and 40°.

17. (Previously Presented) The holder of claim 14, wherein said grinding surface protrudes beyond said outer surface of said clamping part.